



P10

KOROZYON DİRENCİ ISO 9227
CORROSION RESISTANCE ISO 9227

Ürün Product	Saat Hour	(min.)
W2B	72	
W2	72	
W3	200#	
W4	240	
W5	400	

P12

Malzeme sembolü

Material symbol

Ürün Product	Sembol(W...) Symbol(W...)
W2B	W2B
W2	-
W3	-
W4	W4
W5	W5

P11

VİDA KAFA TİPLERİ
SCREW HEAD TYPES

Ürün Product	Philips Tip Philips Type	Slot Tip Slot Type
W2B	X	
W2	X	
W3		X
W4		X
W5		X

PARÇA LİSTESİ / PART LIST

Parça Part	Adet Qty.	Parça Adı Part Name	Malzeme / Material				
			W2B	W2	W3	W4	W5
1	1	Yuva Housing	Yumuşak Çelik * Mild Steel *	1.4016 DIN EN 10088-2	1.4016 DIN EN 10088-2	1.4301 DIN EN 10088-2	1.4401 DIN EN 10088-2
2	1	Vida Screw	Yumuşak Çelik * Mild Steel *	Yumuşak Çelik * Mild Steel *	1.4016 ** DIN EN 10088-3	1.4567 ** DIN EN 10088-3	1.4578 ** DIN EN 10088-3
3	1	Bant Band	1.4016 DIN EN 10088-2	1.4016 DIN EN 10088-2	1.4016 DIN EN 10088-2	1.4301 DIN EN 10088-2	1.4401 DIN EN 10088-2
			veya muadili or equivalent	veya muadili or equivalent	veya muadili or equivalent	veya muadili or equivalent	veya muadili or equivalent

* Çinko Kaplı / Zinc Plated

** Kaplamalı veya Kaplamasız / Plated or Unplated

Sıkma Aralığı Clamp. Range mm Ød-D	Sevkiyat Çapı Shipping Dia. mm Ø+2	W2-W3-W4-W5 Nm			W2B Nm		
		LD max.	AD max.	PD max.	LD max.	AD max.	PD max.
16-25	25	1,2					
16-27	27						
20-32	32						
23-35	35						
25-40	40						
30-45	45	1,0	5,0	6,5	1,2	4,5	5,0
32-50	50						
40-60	60						
50-70	70						
60-80	80						
70-90	90						
80-100	100						
90-110	110						
100-120	120						
110-130	130						
120-140	140						
130-150	150						
140-160	160						
∴	∴						
380-400	400						

LD: Serbest tork / Free torque

AD: Tavsiye edilen uygulama torkü / Recommended tightening torque

PD: Azami test torkü / Maximum test torque